

Self-Organizing Approach for Finding Borders of DNA Coding Regions

Fang Wu¹ and Wei-Mou Zheng²

¹*Department of Physics, Peking University, Beijing 100871, China*

²*Institute of Theoretical Physics, Academia Sinica, Beijing 100080, China*

Abstract

A self-organizing approach is proposed for gene finding based on the model of codon usage for coding regions and positional preference for noncoding regions. The symmetry between the direct and reverse coding regions is adopted for reducing the number of parameters. Without requiring prior training, parameters are estimated by iteration. By employing the window sliding technique and likelihood ratio, a very accurate segmentation is obtained.

PACS number(s): 87.15.Cc, 87.14.Gg, 87.10.+e

The data of raw DNA sequences is increasing at a phenomenal pace, providing a rich source of data to study. As a consequence, we now face the tremendous challenge of extracting information from the formidable volume of DNA sequence data. Computational methods for reliably detecting protein-coding regions are becoming more and more important.

Genome annotation by statistical methods is based on various statistical models of genomic sequences [1, 2], one of the most popular being the inhomogeneous, three-period Markov chain model for protein-coding regions with an ordinary Markov model for noncoding regions. The independent random chain model can be included in this category by regarding it as a Markov chain of order 0. The codon usage model is the independent random chain model of non-overlapping triplets, and corresponds to an inhomogeneous Markov model of order 2. Signals in a short segment are usually buried in large fluctuations. With well chosen parameters statistical models work as a noise filter to pick out the signals.

Methods based on local inhomogeneity, e.g. position asymmetry or periodicity of period 3, suffer fluctuations. Most of the current computer methods for locating genes require some prior knowledge of the sequence's statistical properties such as the codon usage or positional preference [3, 4, 5]. That is, a sizable training set is necessary for estimating good parameters of the model in use [6, 7]. Strongly biased by the training, such models have little power to discover surprising or atypical features. Thus, it is desirable to decipher the genomic information in an objective way. Audic and Claverie [8] have proposed a method which does not require learning of species-specific features from an arbitrary training set for predicting protein-coding regions. They use an *ab initio* iterative Markov modeling procedure to automatically partition genome sequences into direct coding, reverse coding, and noncoding segments. This is an expectation-maximization (EM) algorithm, which is useful in modeling with hidden variables, and is performed in two steps of expectation and maximization [9, 10, 11]. Such a self-organizing or adaptive approach uses all the available unannotated genomic data for its calibration.

Before introducing the model we use and describing the technical details, we explain the EM algorithm with a simple pedagogic model which assumes that a DNA sequence written in four letters $\{a, c, g, t\}$ is generated by independent tosses of two four-sided dice. An annotation maps the DNA sequence site-to-site to a two-letter sequence of the alphabet $\{C, N\}$ (C for coding and N for noncoding). Two sets $\{p_a, p_c, p_g, p_t\}$ and $\{q_a, q_c, q_g, q_t\}$ of positional nucleotide probabilities are associated with the two dice C and N , respectively. The total probability for the given DNA sequence $S = s_1 s_2 \dots$ to be seen under the model is the partition or likelihood function

$$Z = \sum_H P(S|H_\alpha) = \sum_H \prod_i P(s_i|h_i^\alpha), \quad (1)$$

where the summation is over all the possible “annotations” $H = \{H_\alpha\}$ with $H_\alpha = h_1^\alpha h_2^\alpha \dots, h_i^\alpha \in \{N, C\}$, and $P(s|C) = p_s$, $P(s|N) = q_s$. The unknown two sets of probabilities can be determined by maximizing the likelihood Z . From Bayesian statistics

$$P(H_\alpha|S) = \frac{P(S|H_\alpha)P(H_\alpha)}{\sum_H P(S|H_\alpha)P(H_\alpha)}, \quad (2)$$

with prior $P(H_\alpha)$ assumed, the most possible H_α can then be selected as the inferred annotation. As we know, coding regions are organized in blocks. The first simplification is the window coarse-graining. The sequence S is divided into nonoverlapping window segments of constant length w , and each whole window is entirely assigned to either N or C . Conducting Bayesian analysis for window W_j and accepting uniform prior, we have $P(h|W_j) \propto P(W_j|h)$. The second simplification is to introduce “temperature” τ (as in the simulated annealing), replace $P(W_j|h_j)$ with $[P(W_j|h_j)]^{1/\tau}$ and take the limit $\tau \rightarrow 0$. In this way we keep only a single term, i.e. the greatest one, in the summation for Z . Window W is inferred to belong to either N or C depending on whether $P(W|N)$ or $P(W|C)$ is larger. The likelihood maximization is then equivalent to estimating nucleotide probabilities with frequencies in two window classes inferred from the pre-assumed $\{p_s\}$ and $\{q_s\}$. Consistency requires that the estimate probabilities must be equal to $\{p_s\}$ and $\{q_s\}$. This “fixed point” can be found by iteration. As an example, we use the first $99 \times 5051 = 500049$ nucleotides of the complete genome of *E. coli* as the input data. Statistical significance requires that the window size cannot be too small, while a large window size would give poor resolution in discriminating different regions. The window size is chosen to be $w = 99$. We assign the 5051 fixed nonoverlapping windows to the two subsets of N and C in either a periodic or a random way. We estimate p_s and q_s from the counts of different nucleotides in each subset. The likelihood functions for each window are then calculated using the estimated p_s and q_s , and the assignment of the windows to C or N is updated according to which of $P(W|C)$ and $P(W|N)$ is larger. This ends one iteration. The process of iteration converges to a single fixed point of precision 10^{-4} around step 28 for different initializations with a final window assignment to N and C also given. The final p_s and q_s are $\{0.219, 0.270, 0.289, 0.222\}$ and $\{0.279, 0.213, 0.227, 0.281\}$. The q_s estimated from the complete genome are $\{0.285, 0.214, 0.218, 0.283\}$, which are rather close to the corresponding convergent values.

More realistic models take the three phases in the coding regions and the opposite ordering of the direct and reverse coding regions into account. Such models adopt 7 subsets: one for noncoding (N), three for direct coding (C_1, C_2, C_3) and three for reverse coding (C_4, C_5, C_6). The subscript i in C_i indicates the phase 0, 1 or 2 according to $i \pmod{3}$. From the genomic data statistics, we may assume that there is symmetry between the direct and reverse coding regions, which means that a reverse coding sequence is indistinguishable from a direct coding sequence if we make the exchanges $a \leftrightarrow t$, $c \leftrightarrow g$ and reverse the order. For the model based on the positional preference of codons, instead of 7 sets of positional nucleotide probabilities, we need only 4 sets. The reduction of the total number of parameters by the symmetry consideration improves the statistics. The procedure of iteration is similar to that for the last model, the only difference being that now we have to estimate 4 sets of probabilities and calculate 7 likelihood functions for a window.

We use a better model based on the codon usage. We now need a set of 64 probabilities for coding regions. For noncoding segments, 4 positional nucleotide probabilities are used just as before. To simplify the programming, we move the windows with a phase-shift other than zero by one or two nucleotides to clear the phase-shift, although we can calculate the marginal distribution probabilities for uni- and bi-nucleotides. For example, we replace the window $W = s_i s_{i+1} \dots s_{i+w-1}$ marked as C_2 with $W' = s_{i+1} s_{i+2} \dots s_{i+w}$. (The alternative way is to consider a cyclic transformation.) Our further discussions are all based on this model. It is observed that the iteration also quickly converges to a fixed point. Contrary to the two-sets model where coding and noncoding are symmetric, and extra knowledge is required to relate one set to coding and the other to noncoding, we can now distinctly distinguish coding from noncoding regions, even with their phases fixed. Direct and reverse coding sets are symmetric in the model. However, the fact that stop codons *taa*, *tag* and *tga* are rare can be used to remove the symmetry between direct and reverse coding. That is, if the convergent probabilities for *taa*, *tag* and *tga* are all significantly small in comparison with the other 61, sets C_1, C_2 and C_3 then do indeed correspond to direct coding. (Otherwise, those of *tta*, *cta* and *tca* would be small instead.)

We employ the sliding window technique to improve the resolution as follows. We shift each window

by 3 nucleotides, initiate the window assignment with the convergent probabilities just obtained, and then find new assignments for the shifted windows by iteration. We repeat the shifting process 32 times to cover the window width. This ends with 33 assignments for triplets, except for a few sites at the two ends. By a majority vote we can obtain a triplet assignment of the whole sequence.

Recently, an entropic segmentation method that uses the Jensen-Shannon measure for sequences of a 12-letter alphabet has been proposed to find borders between coding and noncoding regions [12]. Their best result was obtained on the genome of the bacterium *Rickettsia prowazekii*. We test our approach with the same genome data. To inspect the accuracy we obtain the “true” assignment of sites based on the known annotation as follows. If a nucleotide is in a noncoding region, it belongs to N. If it is in a coding (or reverse coding) region and the site-index of the beginning nucleotide plus 1 is congruent to i modulo 3, the nucleotide under consideration will belong to C_{1+i} (or C_{4+i}). For overlapping coding zones we may keep two alternative assignments. We define three rates of accuracy R_2 , R_3 and R_7 : R_2 only discriminates coding from noncoding segments while R_7 covers full discrimination of the 7 sets, and R_3 ignores the phases. For the total $N = 1\,111\,523$ nucleotides, we obtain $R_2 = 91.7\%$, $R_3 = 89.8\%$ and $R_7 = 89.7\%$. (The rates without window sliding are $R_2 = 89.1\%$, $R_3 = 84.8\%$ and $R_7 = 84.4\%$.)

For finding block borders, to eliminate illusary fluctuations we accept only the assignments with the 33 identical samplings, and regard others as undetermined. When two adjacent identified blocks are of the same assignment we join the two together with the sites between into a single zone of the same assignment. Otherwise, we take the middle site of the intervening undetermined zone as the border, and assign the two sides according to their corresponding flank blocks. We can do the job better by means of the likelihood ratio. Suppose that the left block is assigned to l , and the right to r . A point m in the intervening zone divides the zone into two segments L_m and R_m . The likelihood ratio is defined as

$$\Gamma_m = \frac{P(L_m|l)P(R_m|r)}{P(L_m|r)P(R_m|l)}. \quad (3)$$

The maximal Γ_m places the border at m . This segmentation finally gives the accuracy rates $R_2 = 93.3\%$, $R_3 = 92.8\%$ and $R_7 = 92.7\%$.

In Ref. [12] the quantity quantifying the coincidence between borders inferred from the segmentation and those from the known annotation is defined by

$$D = \frac{1}{2N} \left[\sum_i \min_j |b_i - c_j| + \sum_j \min_i |b_i - c_j| \right], \quad (4)$$

where $\{b_i\}$ is the set of all borders between coding and noncoding regions, and $\{c_j\}$ is the set of all cuts produced by the segmentation. We use an even harsher quantity D by interpreting $\{b_i\}$ and $\{c_j\}$ as the borders of all coding zones. That is, we include borders of each overlapping coding zone. The total number of “CDS” in the annotation is 834, one of which has two joint zones. We obtain $1 - D = 87.7\%$, compared with $\sim 80\%$ of Ref. [12]. In Fig. 1 we show a comparison of the inferred segmentation with the known coding regions. In the section from 475 500 to 497 500 there are two overlaps (one for direct, and the other for reverse coding regions), and the shortest gap separating adjacent coding regions is just 1 nucleotide (at 486 215). They do not escape detection. As mentioned in [12], there are two very close coding regions in the same phase (538 197 : 539 879 and 539 937 : 540 887). The result from the majority vote is shown in Fig. 2 for the section. We see indeed a peak of the counts for set N between the two coding regions. The highest count for N is 32, and so is ignored in our strategy. There is indeed plenty of room for improving this approach. A larger width $w = 123$ gives higher accuracy rates: $R_2 = 93.6\%$, $R_3 = 93.3\%$, $R_7 = 93.0\%$ and $1 - D = 88.2\%$. When we consider only the triplets with all 33 assignments identical in window sliding the rates are $R_2 = 98.7\%$, $R_3 = 98.6\%$ and $R_7 = 98.6\%$. In the above we avoid setting up an arbitrary cut-off threshold. If a threshold of 17 counts is used to determine the segments whose central parts have 33 identical samplings, for $w = 99$ we predict a total of 1 001 351 (90.1%) sites with accuracies $R_2 = 97.4\%$ and $R_3 = 95.4\%$. The accuracy rate for noncoding regions is 96.5%, much higher than that of Ref. [8]. It is important and feasible to integrate biological signals into our algorithm. We expect our algorithm, with certain modifications, should work well for other species, too.

This work was supported in part by the Special Funds for Major National Basic Research Projects, the National Natural Science Foundation of China and Research Project 248 of Beijing.

References

- [1] J.W. Fickett, Comput. Chem. **20**, 103 (1996).
- [2] J.W. Fickett and C.S. Tung, Nucleic Acids Res. **20**, 6441 (1992).
- [3] R. Grantham, C. Gautier, M. Gouy, M. Jacobzone, and R. Mercier, Nucleic Acids Res. **9**, 0 R43 (1981).
- [4] J. W. Fickett, Nucleic Acids Res. **10**, 5303 (1982).
- [5] S. Karlin and J. Mrazek, J. Mol. Biol. **262**, 459 (1996).
- [6] M. Borodovsky and J. D. McIninch, Comput. Chem. **17**, 123 (1993).
- [7] M. Borodovsky, J. D. McIninch, E. V. Koonin, K. E. Rudd, C. Medigue, and A. Danchin, Nucleic Acids Res. **23**, 3554 (1995).
- [8] S. Audic and J.-M. Claverie, Proc. Natl. Acad. Sci. USA, **95**, 10026 (1998).
- [9] P. Baldi, Bioinformatics **16**, 367 (2000); P. Baldi and S. Brunak, *Bioinformatics: The Machine Learning Approach* (The MIT Press, Cambridge, Ma., 1998).
- [10] C. E. Lawrence and A. A. Reilly, Proteins **7**, 41 (1990).
- [11] L. R. Cardon and G. D. Stormo, J. Mol. Biol. **223**, 159 (1992).
- [12] P. Bernaola-Galván, I. Grosse, P. Carpena, J.L. Oliver, R. Román-Roldán, and H.E. Stanley, Phys. Rev. Lett. **85**, 1342 (2000).

Figure 1: Comparison between the inferred segmentation (dotted lines) and the known coding regions of *Rickettsia* (shaded areas).

Figure 2: Counts of majority assignment in the section containing two very close coding regions (shaded areas) in the same phase. A peak corresponding to noncoding assignment is clearly seen.



